

DVSHD

HD compact video player



Golding Audio Ltd

The DVSHD is a powerful yet easy to use commercial HD (High Definition) digital media player designed for looping playback and triggered playback of MPEG-1/2/4 video files and high resolution still pictures in commercial environments.

The videos and pictures are stored and played directly from a SD memory card or USB memory stick. The DVSHD supports many resolutions including 1080P 60Hz through HDMI output.

Typical Applications: Interactive kiosks
Theme park attractions
Point Of Sale
In-vehicle video systems
Digital signage
Museum Display

Features:

- 1080P output resolution
- Cost effective
- Compact unit with integral fixing points
- Screw terminals for ease of installation
- Line out for driving external amplifiers
- 8 direct access trip inputs
- Power Supply included
- Supports many file formats
- RS232 control
- Autoplay on power up
- Watchdog monitoring

Supported format :

Video formats

MPEG1 / MPEG2 / MP4 (H264) / Motion Jpeg

Video file extensions

MP4 / MOV / M4V / MKV / TS / MTS / M2S / DAT / MPG / MPEG / VOB / ISO

Still image formats

JPEG / BMP / TIFF / PNG / GIF

Audio formats

MPEG1/2 / MP3 / WMA / AC3 / LPCM

Modes of operation :

- Autoplay on power up (No trips)
- Autoplay on power up (Triggered)
- Fast mode
- Slideshow mode

Interactivity :

- 8 trip inputs
- Motion sensor
- Serial port control

Specifications:

Storage Media	SD card (SD, SDHC, SDXC) / USB Memory stick / USB HD
Storage format	FAT / FAT32 / NTFS
Video formats	MPEG1 / MPEG2 / MP4 (H264) / Motion Jpeg
Video file extensions	MP4 / MOV / M4V / MKV / TS / MTS / M2S / DAT / MPG / MPEG / VOB / ISO
Still image formats	JPEG / BMP / TIFF / PNG / GIF
Audio formats	MPEG1/2 / MP3 / WMA / AC3 / LPCM
Video Output	HDMI 1080P 60/50Hz 1080i 60/50Hz 720P 60/50Hz 576P, 480P, PAL, NTSC Composite
Aspect Ratio	Pan Scan 4:3, Letter Box 4:3, 16:9, 16:10
Audio Output	Line level (3.5mm jack) Digital Optical
External trips	8 trip inputs (5v pullups, switch to ground)
Serial control	RS232 9600 8N1
Power	12VDC @ 500mA
Dimensions (WxDxH)	157mm x 118mm x 29mm
Compliance	RoHS, CE/FCC



www.goldingaudio.co.uk